


KGL100P Series NiCd 100Ah



www.germarel.de

CONSTRUCTION:

Alkaline nickel-cadmium cell consists of pocket plate positive oxide-nickel and negative cadmium electrodes, divided by plastic separators, which provide stable spark gap and free circulation of electrolyte.



- 1. Terminal** - provides the current takeoff and cell connection.
- 2. Plug** - provides convenient electrolyte filling, free gas outlet during charging, and excludes electrolyte splashing and its aerosol steams.
- 3. Electrode connection** - connects the electrodes and provides the current transfer from electrodes to terminal.
- 4. Contact banks** - are welded to electrode and provide the current takeoff from the electrodes.
- 5. Electrode** - consists of horizontally located pocket plates, contains active material enclosed in steel perforated strip.
- 6. Rib** - provide electrode rigidity and current transfer to the contact banks.
- 7. Frame separator** - divides positive and negative electrodes, provides free circulation of electrolyte between the electrodes.

KGL100P Series NiCd 100Ah



www.germarel.de

Electrolyte requirements:

Electrolyte is a water solution of potassium hydroxide GOST 9285-78 of superior grade with density $(1200 \pm 10) \text{ kg/m}^3$, $(1,19 - 1,21 \text{ g/cm}^3)$ with addition of lithium hydroxide GOST 8595-83 in amounts of $(20 \pm 1) \text{ g/l}$. At the electrolyte temperature less than $-30 \text{ }^\circ\text{C}$ use electrolyte with density $1,26 - 1,28 \text{ g/cm}^3$ without addition of lithium hydroxide.

General characteristics:

- Batteries are supplied in the form of separate cells or battery blocks with compounds;
- Nominal voltage of cell is 1,2V, the block voltage depends on the number of the cells in the block (2,4 V; 3,6 V; 4,8 V; 6,0 V; 7,2 V; 8,4 V; 9,6 V; 10,8 V; 12,0 V);
- Cells and batteries provide full operation after storage during three months within the whole working temperature range without charge when putting into operation, under condition, that battery was charged and powered off before placing in storage;
- Cells and batteries ensure operation after six months storage, under condition, that battery was charged and powered off before placing in storage, battery should be charged before starting operation;
- Criterion of cells limiting state is a lowering of available capacity to less than 60 % of nominal capacity;

After completion of operation, Germarel accept cells for recycling together with electrolyte.



KGL100P Series NiCd 100Ah



www.germarel.de

MAINTENANCE-FREE ALKALINE NICKEL-CADMIUM CELLS OF KGL TYPE AND BLOCKS OF THEM

The cells of KGL type are alkaline cells with gas recombination and comply with international standard IEC 62259. These cells don't require periodic correction of electrolyte level when operated at long charge rate by low current or under specified stabilized charge voltage.

APPLICATIONS:

- Back-up power for cellular base stations, wire automatic telephone systems and other telecommunication objects;
- Signaling systems; emergency lighting and electrical power supply;
- Solar and wind power objects;
- Oil and gas complex (recovery, transportation and refining);
- Electric power objects (generation and distribution);
- Power systems of navigation marks;
- Underground;
- Passenger railway carriages;
- Electric locomotives and electric trains;
- Urban electric transport;
- Sea and river ships.

It's possible to develop and supply battery blocks with the different number of cell and individual layout according to customer's technical requirements.

Appearance of KGL type cells



KGL45P
KGL60P



KGL70P



KGL100P
KGL125P
KGL140P



KGL160P



KGL200P
KGL250P
KGL300P

KGL100P Series NiCd 100Ah



www.germarel.de

Range and main characteristics of KGL type cells

| Cell type | IEC 62259 designation | Nominal capacity, C5 | Cell dimensions, mm | | | Cell weight with electrolyte, kg | Terminals |
|-----------|-----------------------|----------------------|---------------------|------|-----|----------------------------------|-----------|
| | | | W | L | H | | |
| KGL60P | KGL60P | 60 | 113 | 59 | 270 | 2,9 | M10 |
| KGL70P | KGL70P | 70 | 127 | 62,5 | 282 | 4,0 | M14 |
| KGL100P | KGL100P | 100 | 137 | 78 | 360 | 5,8 | M10 |
| KGL125P | KGL125P | 125 | 137 | 78 | 360 | 6,1 | M10 |
| KGL140P | KGL140P | 140 | 137 | 78 | 362 | 6,5 | M14 |
| KGL160P | KGL160P | 160 | 137 | 113 | 327 | 8,5 | M16 |
| KGL200P | KGL200P | 200 | 171 | 118 | 356 | 11,4 | M20 |
| KGL200P | KGL200P | 200 | 171 | 118 | 370 | 11,4 | M20 |
| KGL250P | KGL250P | 250 | 171 | 118 | 356 | 12,0 | M20 |
| KGL250P | KGL250P | 250 | 171 | 118 | 370 | 12,0 | M20 |
| KGL300P | KGL300P | 300 | 171 | 118 | 356 | 12,4 | M20 |
| KGL300P | KGL300P | 300 | 171 | 118 | 370 | 12,4 | M20 |
| KGL300P | KGL300P | 300 | 172 | 119 | 405 | 13,2 | M20 |
| KGL350P | KGL350P | 350 | 171 | 174 | 370 | 17,9 | M20 |
| KGL400P | KGL400P | 400 | 169 | 174 | 411 | 19,2 | 2×M16 |
| KGL450P | KGL450P | 450 | 169 | 174 | 411 | 19,9 | 2×M16 |
| KGL500P | KGL500P | 500 | 169 | 174 | 411 | 20,0 | 2×M16 |

KGL100P Series NiCd 100Ah



www.germarel.de

Blocks Dimensions


| Cell type | Block dimensions, mm | | | | | | | | | | |
|-----------|----------------------|-----|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| | W | H | L / L1 | | | | | | | | |
| | | | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| KGL45P | 138 | 280 | 148 | 207 | 266 | 325 | 399 | 458 | 517 | 576 | 635 |
| KGL60P | 138 | 280 | 148 | 207 | 266 | 325 | 399 | 458 | 517 | 576 | 635 |
| KGL70P | 150 | 295 | 155 | 218 | 280 | 343 | 420 | 483 | 545 | 608 | 670 |
| KGL100P | 170 | 370 | 192 / 230 | 270 / 308 | 348 / 386 | 426 / 464 | 522 / 560 | 600 / 638 | 678 / 716 | 756 / 794 | 834 / 872 |
| KGL125P | 170 | 370 | 192 / 230 | 270 / 308 | 348 / 386 | 426 / 464 | 522 / 560 | 600 / 638 | 678 / 716 | 756 / 794 | 834 / 872 |
| KGL140P | 170 | 370 | 192 / 230 | 270 / 308 | 348 / 386 | 426 / 464 | 522 / 560 | 600 / 638 | 678 / 716 | 756 / 794 | 834 / 872 |
| KGL160P | 170 | 338 | 262 | 375 | 488 | 601 | - | - | - | - | - |
| KGL200P | 205 | 370 | 270 | 388 | 506 | 624 | - | - | - | - | - |
| KGL200P | 205 | 384 | 270 | 388 | 506 | 624 | - | - | - | - | - |
| KGL250P | 205 | 370 | 270 | 388 | 506 | 624 | - | - | - | - | - |
| KGL250P | 205 | 384 | 270 | 388 | 506 | 624 | - | - | - | - | - |
| KGL300P | 205 | 370 | 270 | 388 | 506 | 624 | - | - | - | - | - |
| KGL300P | 205 | 384 | 270 | 388 | 506 | 624 | - | - | - | - | - |
| KGL300P | 205 | 419 | 272 | 391 | 510 | 629 | - | - | - | - | - |
| KGL350P | 205 | 380 | 382 / 437 | 556 / 611 | - | - | - | - | - | - | - |

KGL100P Series NiCd 100Ah



www.germarel.de

KGL100P Drawing



KGL100P Series NiCd 100Ah



www.germarel.de

